


# STONECREST® SLATE

## STEEL SHINGLE

## PRODUCT DATA



Manufactured in Joplin, MO

**METALWORKS® STONECREST® SLATE** is made of heavier gauge steel and has been double stamped for a more dramatic slate look that closely replicates the random finish of natural slate. Available in a beautiful array of colors.

### USES

For application to roof decks with inclines not less than 3 inches per foot and up to mansard or sidewall application. For slopes between 3 and 4 inches per foot, TW Metal & Tile Underlayment or TW Underlayment must be used over entire deck area.

### ADVANTAGES

- Backed by a 50 Year Limited Product Warranty, 25 Year Full Start Period, Limited Transferability, a 30 Year Finish Limited Warranty, and a 50 Year Limited Wind Warranty against damage from winds up to 110 mph.\*
- Galva-Strength G-90 steel construction.
- Special coating process resists dirt and environmental aging. Fluoropolymer coating system from The Valspar® Corporation with Kynar® 500/Hylar 5000® coating.
- Lightweight compared to traditional roofing products.
- Resists fading and chalking.
- Fire resistant for added protection.\*\*
- Can be applied over existing asphalt shingles eliminating disposal cost and mess.\*\*\*
- Four-way locking system for enhanced performance.

\*For information regarding or a copy of TAMKO's limited warranty, contact your local TAMKO representative, visit us online at [www.tamko.com](http://www.tamko.com), or call us at 800-641-4691.

\*\*Contact TAMKO or Underwriters Laboratories for specific application requirements for U.L. Class A rated systems.

\*\*\*Check your Local Building Code. Building Code restrictions may apply.

### COLORS

StoneCrest Slate Colors:

- Quaker Green
- Sierra Slate Grey
- Vermont Blue
- Sequoia Red

### CERTIFICATION/REPORTS

Listed by UL for:

Class A Fire Rating\*\*

Wind Resistance

Impact Resistance, Class 4

ICC-ES ESR-1129

Accepted for Use, City of New York, Department of Buildings MEA 156-00-M Vol II

CCMC 13011-R

Tested in compliance with:

UL 790

ASTM D 3161, Class F (110 MPH)

UL 2218

### PRODUCT DATA†

Shingle Size: 12-5/8" x 39-3/4"

Exposure: 12"


Coverage per Box: 49.2 sq ft  
(approx. 1/2 sq)

Shingles per Box: 15

Shingles per Square: 30

Weight per Shingle: 2.5 lbs

Weight per Square: 74 lbs



Shingle material: Nominal 0.0162" thickness, including G-90 galvanization and paint coatings.


Exterior finish: Fluoropolymer (PVDF) with anti-corrosive primer, 1 mil dry film thickness.

Interior finish: Wash coat with anti-corrosive primer, 0.6 mil dry film thickness.

Clip: 1-1/4" wide x 2-1/8" long x 1/5" deep

Clip Material: 0.015" thick, G-90 galvanized steel

Refer to Accessory Product Data Sheet for more information.



†All values stated as nominal

## METALWORKS

STEEL SHINGLES



Visit our Web Site at [www.tamko.com](http://www.tamko.com) or [www.metalworksroof.com](http://www.metalworksroof.com)

08/01/2006

Central District	220 West 4th St., Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr., Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St., Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp., Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave., Denver, CO	80216	800-530-8868

METALWORKS, StoneCrest and TAMKO are registered trademarks of TAMKO Building Products, Inc. Fluoropon® and Valspar® are registered trademarks of The Valspar Corporation, Inc. Kynar® is a registered trademark of Arkema, Inc. Hylar 5000® is a registered trademark of Solvay Solexis, Inc.

© 2006 TAMKO Building Products, Inc.  
JP53130



997802